



ELENCO PARTI				
ELEMENTO	QTÀ	NUMERO PARTE	DESCRIZIONE	Description
1	1	00103101N	Basamento	Base
2	2	141610	Boccola	Bushing
3	1	00103103N	Albero fresato 08 mm	Milled shaft 08 mm
4	1	P304207	Paraolio	Oil seal
5	1	MA-6A-MUN	Puleggia Ogura 108 Nm	Ogura pulley 108 Nm
6	3	TBEI 6 x 16	Viti testa a bottone	Button head screws
7	1	TE 8 x 30	Vite a testa esagonale	Screw head hexagonal
8	1	§ 8	Rondella piana	Flat washer
9	2	Seeger	Seeger	Seeger
10	1	4 x 6,5	Chiavetta	Key
11	1	SKF 6005-2RSH	Cuscinetto a sfere	Ball bearing
12	1	SKF 6205-2RSH	Cuscinetto a sfere	Ball bearing

CARATTERISTICHE TECNICHE		TECHNICAL FEATURES	
Tensione di alimentazione		Exciting voltage	Volt 12
Assorbimento		Absorption	Amp. 3.7
Consumo energetico massimo		Power consumption	Watt 47
Velocità massima		Max speed	Rpm 6000
Trazione		Static torque	Nm 108
Diametro puleggia		Diameter pulley	mm 152
Tipo puleggia		Type pulley	Vbelt 2
Giunto fresato	8mm	Milled joint	8mm
Cetraggio	§52mm	Centering	§52mm