



ELENCO PARTI				
ELEMENTO	QTÀ	NUMERO PARTE	DESCRIZIONE	Description
1	1	00103101N	Basamento	Base
2	2	141610	Boccola	Bushing
3	1	00103103N	Albero fresato 08 mm	Milled shaft 08 mm
4	1	P304207	Paraolio	Oil seal
5	3	TBEI 6 x 16	Viti testa a bottone	Buttong head screws
6	1	TE 8 x 35	Viti a testa esagonale	Screws head hexagonal
7	1	§ 8	Rondella piana	Flat washer
8	2	Seeger	Seeger	Seeger
9	1	4 x 6,5	Chiavetta	Key
10	1	SKF 6005-2RSH	Cuscinetto a sfere	Ball bearing
11	1	MA-N05-MUN-M	Puleggia Ogura 108 Nm modificata	Ogura 108 Nm pulley modified
12	1	SKF 6205-2RSH	Cuscinetto a sfere	Ball bearing

CARATTERISTICHE TECNICHE		TECHNICAL FEATURES	
Tensione di alimentazione		Exciting voltage	Volt 12
Assorbimento		Absorbition	Amp. 3.7
Consumo energetico massimo		Power consumption	Watt 47
Velocità massima		Max speed	Rpm 6000
Trazione		Static torque	Nm 108
Diametro puleggia		Diameter pulley	mm 156
Tipo puleggia		Type pulley	poliV 6
Giunto fresato	8mm	Milled joint	8mm
Centraggio	§52mm	Centering	§52mm