



| ELENCO PARTI | | | | |
|--------------|-----|---------------|------------------------|----------------------|
| ELEMENTO | QTÀ | NUMERO PARTE | DESCRIZIONE | Description |
| 1 | 1 | 00105101N | Basamento | Base |
| 2 | 2 | 141610 | Boccola | Bushing |
| 3 | 1 | 00105105N | Albero fresato 10 mm | Milled shaft 10 mm |
| 4 | 1 | Seeger | Seeger | Seeger |
| 5 | 1 | MA-N05-MUN-8 | Pulaggia Ogura 108 Nm | Ogura pulley 108 Nm |
| 6 | 3 | TBEI 6 x 16 | Viti testa a bottone | Button head screws |
| 7 | 1 | TE 8 x 35 | Vite a testa esagonale | Hexagonal head screw |
| 8 | 1 | § 8 | Rondella piana | Flat washer |
| 9 | 1 | 4 x 6,5 | Chiavetta | Key |
| 10 | 2 | SKF 6205-2RSH | Cuscinetto a sfere | Ball bearing |

| CARATTERISTICHE TECNICHE | | TECHNICAL FEATURES | |
|----------------------------|-------|--------------------|----------|
| Tensione di alimentazione | | Exciting voltage | Volt 12 |
| Assorbimento | | Absorbition | Amp. 3.7 |
| Consumo energetico massimo | | Power consumption | Watt 47 |
| Velocità massima | | Max speed | Rpm 6000 |
| Trazione | | Static torque | Nm 108 |
| Diametro puleggia | | Diameter pulley | mm 140 |
| Tipo puleggia | | Type pulley | poliV 7 |
| Centraggio | §32mm | Centering | §32mm |