



| N° | Q | CODICE/CODE | DESCRIZIONE         | DESCRIPTION       |
|----|---|-------------|---------------------|-------------------|
| 1  | 1 | 00125103    | Albero              | Shaft             |
| 2  | 1 | 17.2X25X4   | Boccola             | Bushing           |
| 3  | 1 | I 40        | Seeger              | Seeger            |
| 4  | 1 | SKF 3203    | Cuscinetto a sfera  | Ball bearing      |
| 5  | 1 | 00125101    | Basamento           | Base              |
| 6  | 1 | 00120102    | Mozzo               | Brachet           |
| 7  | 3 | M6 x 20     | Vite svasata        | Countersunk screw |
| 8  | 2 | 141610      | Boccola             | Bushing           |
| 9  | 1 | 4 x 10      | Spina elastica      | Spring pin        |
| 10 | 1 | 00120104    | Boccola             | Bushing           |
| 11 | 1 | 53724700-4  | Frizione OGURA 60Nm | OGURA Clutch 60Nm |
| 12 | 1 | 4 x 4 x 16  | Chiavetta           | Key               |
| 13 | 1 | 8X20X4      | Rondella piana      | Washer            |
| 14 | 1 | M8 x 25     | Vite esagonale      | Exagonal screw    |

| CARATTERISTICHE TECNICHE   |                   | TECHNICAL FEATURES |      |
|----------------------------|-------------------|--------------------|------|
| Tensione di alimentazione  | Exciting voltage  | Volt               | 12   |
| Assorbimento               | Absorbition       | Amp.               | 3.7  |
| Consumo energetico massimo | Power consumption | Watt               | 47   |
| Velocità massima           | Max speed         | Rpm                | 6000 |
| Trazione                   | Static torque     | Nm                 | 60   |
| Diametro puleggia          | Diameter pulley   | mm                 | 120  |
| Tipo puleggia              | Type pulley       | poliV              | 5    |